

STEINEL®

HL 1802 E



(USA) Operator's use & care manual

Read this use & care manual before using. Keep for future reference. Save this Manual.

(F) Manuel d'emploi et de service

Ce manuel d'emploi et de service est à lire avant l'usage. Garder pour future référence. Conservez ce manuel.

(E) Instrucciones de uso y mantenimiento

Leer estas instrucciones de uso y mantenimiento antes de utilizar la pistola. Conservarlas para futuras consultas.



Listed
Hot Air Gun



UL WARNING Read this instruction book before using. To reduce risk of fire or electric shock, do not expose to rain or moisture. Store indoors. When servicing, use only identical replacement parts. When using electronic tools, basic safety precautions should always be followed to reduce the risk of fire, electric shock and personal injury. This hot air gun operates at 1100° F with no visual indication of temperature (no flame). The hot airstream at the outlet nozzle will burn flesh. Do not turn on hot air gun with hand in front of nozzle. **DO NOT USE NEAR COMBUSTIBLE LIQUIDS. DO NOT USE FOR:** ● Heating gas engines ● Heating car batteries ● Thawing refrigerator equipment.

Cautions

1. This hot air gun can produce up to 1100° of flameless heat at the nozzle. Do not direct airstream at clothing, hair or other body parts. Do not use as a hair dryer.
2. Do not use near flammable liquids or in an explosive environment (fumes, gases or dust). Remove materials or debris, that may become ignited, from work area.
3. Always hold tool by plastic enclosure. The metal nozzle requires approximately 20 minutes to cool to where it can be touched. Do not touch nozzle or accessory tips until cool.
4. Do not store tool until nozzle has cooled to room temperature. Place tool in a clear area away from combustible materials while cooling.
5. Do not cut off air flow by placing nozzle too close to workpiece. Keep intake vents clean and clear of obstructions.
6. Place tool on a level surface with the support stand firmly in place when tool is not hand held. Place cord in a position that won't cause tipping.
7. Do not leave tool unattended while running or cooling down.
8. Keep a fully charged fire extinguisher nearby.
9. Do not direct air flow directly on glass.
10. Shield materials around the heated area to prevent damage or fire.
11. Use only with 120 V AC voltage.
12. Do not use in wet conditions.
13. Not to be used by children. This is not a toy and should be respected.
14. Do not use in bath or over water.
15. Safety glasses should be worn when using this tool.
16. For stripping paint, see detailed instructions in this manual.
17. It is recommended that leather gloves be worn when using a hot air gun.

WARNING!

This tool is capable of producing temperatures up to 1100° F of flameless heat at the nozzle. ALWAYS:

- Direct the heat away from yourself and others.
- Prevent ignition of combustible materials on or near the workpiece.
- Prevent blockage of intake and nozzle openings.
- Keep a fully charged fire extinguisher on hand.
- Allow the nozzle and accessory tips to cool to room temperature before storage.

**IMPORTANT SAFETY INSTRUCTIONS
READ THESE INSTRUCTIONS**

WARNING: Hidden areas such as behind walls, ceilings, floors, soffit boards and other panels may contain flammable materials that could be ignited by the hot air gun when working in these locations. The ignition of these materials may not be readily apparent and could result in property damage and injury to persons. Do not use if in doubt about this hazard. When working in these locations, keep the hot air gun moving in a back-and-forth motion. Lingering or pausing in one spot could ignite the panel or the material behind it. The hot air gun should be used on LOW temperature which is approximately at # 8 on the temperature dial.

Paint Stripping

WARNING: Extreme care should be taken when stripping paint. The peelings, residue and vapors of paint may contain lead, which is poisonous. Any pre-1977 paint may contain lead and paint applied to homes prior to 1950 is likely to contain lead. Once deposited on surfaces, hand to mouth contact can result in the ingestion of lead. Exposure to even low levels of lead can cause irreversible brain and nervous system damage; young and unborn children are particularly vulnerable.

Before beginning any paint removal process you should determine whether the paint you are removing contains lead. This can be done by your local health department or by a professional who used a paint analyzer to check the lead content of the paint to be removed. **LEAD-BASED PAINT SHOULD ONLY BE REMOVED BY A PROFESSIONAL AND SHOULD NOT BE REMOVED USING A HOT AIR GUN.**

Persons removing paint should follow these guidelines.

1. Move the work piece outdoors. If this is not possible, keep the work area well ventilated. Open the windows and put an exhaust fan in one of them. Be sure the fan is moving the air from inside to outside.
2. Remove or cover any carpets, rugs, furniture, clothing, cooking utensils and air ducts.
3. Place drop cloths in the work area to catch any paint chips or peelings. Wear protective clothing such as extra work shirts, overalls and hats.
4. Work in one room at a time. Furnishings should be removed or placed in the center of the room and covered. Work areas should be sealed off from the rest of the dwelling by sealing doorways with drop cloths.
5. Children, pregnant or potentially pregnant women and nursing mothers should not be present in the work area until the work is done and all clean up is complete.
6. Wear a dust respirator mask or a dual filter (dust and fume) respirator mask which has been approved by the Occupational Safety and Health Administration (OSHA), the National Institute of Safety and Health (NIOSH), or the United States Bureau of Mines. These masks and replaceable filters are readily available at major hardware stores. Be sure the mask fits. Beards and facial hair may keep masks from sealing properly. Change filters often. DISPOSABLE PAPER MASKS ARE NOT ADEQUATE.
7. Use caution when operating the hot air gun. Keep the hot air gun moving as excessive heat will generate fumes which can be inhaled by the operator.
8. Keep food and drink out of the work area. Wash hands, arms and face and rinse mouth before eating or drinking. Do not smoke or chew gum or tobacco in the work area.
9. Clean up all removed paint and dust by wet mopping the floors. Use a wet cloth to clean all walls, sills and any other surface where paint or dust is clinging. DO NOT SWEEP, DRY DUST OR VACUUM. Use high phosphate detergent or trisodium phosphate (TSP) to wash and mop areas.
10. At the end of each work session put the paint chips and debris in a double plastic bag, close it with tape or twist ties, and dispose of properly.
11. Remove protective clothing and work shoes in the work area to avoid carrying dust into the rest of the dwelling. Wash work clothes separately. Wipe shoes off with a wet rag that is then washed with the work clothes. Wash hair and body thoroughly with soap and water.

SAVE THESE INSTRUCTIONS

Double Insulated Tools

Tools marked with the words "Double Insulated" are equipped with a two prong plug. These tools have a special insulation system that complies with applicable standards of both Underwriter's Laboratories, Inc. and Canadian Standard Association. They do not require grounding.

Extension Cords

Double insulated tools, like this one, have two prong cords and can use either a two or three prong extension cord. As the distance from the supply outlet increases, however, heavier gauge extension cords are required.

The use of extension cords of inadequate size wire causes a serious drop in voltage and loss of power. Protect the cord from damage. Keep cords away from excessive heat, sharp edges and damp or wet areas. Repair or replace damaged extension cords before using.

Ext. Cord Length	Wire Size
40 Ft.	16
85 Ft.	14
100 Ft.	12
170 Ft.	10
270 Ft.	8
400 Ft.	6
650 Ft.	4

Limited Warranty

Steinel America, Inc., (the "Company") warrants for one year from the date of purchase, its products to be free from defective material and workmanship, within generally accepted industry standards. The liability of the Company under this warranty shall be limited, at the Company's option, to the repair or replacement of any product found to be defective within the meaning of this warranty. The purchaser should send the product, postage pre-paid, to the Company's shop. The Company shall be liable for no other damages or losses.

This warranty does not apply where: (1) repairs or attempted repairs have been made by others; (2) repairs are required because of normal wear and tear; (3) the tool has been abused, misused, or improperly maintained; or (3) alterations have been made to the tool.

THE WARRANTY DESCRIBED HEREIN SHALL BE IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

THE PARTIES AGREE THAT THE PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE COMPANY SHALL BE FOR THE REPAIR OR REPLACEMENT OF THE TOOL, AS PROVIDED FOR HEREIN. PURCHASER AGREES THAT NO OTHER REMEDY (INCLUDING, BUT NOT LIMITED TO, ACTIONS FOR ACTUAL DIRECT LOSS OR DAMAGE, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR LOST PROFITS, LOST SALES, INJURY TO PERSON OR PROPERTY OR

ANY OTHER ACTUAL, DIRECT, INCIDENTAL OR CONSEQUENTIAL LOSS SHALL BE AVAILABLE TO PURCHASER.

Any and all other statements about the merchandise being purchased under this contract, whether oral or written, do not constitute a warranty, and shall not be relied upon by the purchaser, and are not part of the contract for sale. The entire contract is embodied in this writing. This writing constitutes the final expression of the parties' agreement and is a complete and exclusive statement of the terms of that agreement.


This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

STEINEL America Inc.
9051 Lyndale Avenue South
Bloomington, MN 55420
Tel.: 612-888-5950
Fax: 612-888-5132
Toll-free: 1-800-852-4343

STEINEL Canada Inc.
108-3070 Norland Avenue
Burnaby B. C.
V5B 3A6
Tel.: (604) 299-3506
Fax: (604) 299-1222



Operating Instructions HL 1802 E



To operate the Steinel HL 1802 E hot air gun, plug the cord into a 120 V a. c. power source. Be sure the power switch is in the OFF position. The HL 1802 E has a four position power switch (see "switch" above). Be sure the unit is pointed away from yourself and materials before turning the unit on. The temperature can be adjusted by rotating the thumb wheel on the rear of the unit. Number 1 is 120° F and number 15 1100° F. No precise temperature designation is assigned to numbers on the dial. The unit may be used in a hand held position (Fig. 1) or in a hands free, upright position (Fig. 2) on a flat level surface. When using the unit in the upright position, be sure the cord is placed in such a position that it will prevent tipping the hot air gun over, pulling the hot air gun off the work surface or causing tripping over the cord. The hot air gun provides a low velocity stream of hot air providing rapid heating for applications such as stripping paint, thawing frozen pipes, forming plastics, soldering copper pipe and applying heat shrinkable tubing. The proper amount of heat for each application is dependent upon temperature range selected distance between nozzle and workpiece and length of time heat is applied. The recommended procedure is to experiment with scrap materials and start with lowest temperature range. Use care in approaching the work until the proper combination of heat, distance and time of application has been obtained. It is generally best to use a gentle back-and-forth motion when applying heat unless it has been determined that a concentrated heat is desirable.

Technical Specifications

Voltage: 120 volts AC

Output: 1500 watts

Temperature: Step 1: 120° F
Step 2: (120° F - 1100° F)
















Air flow: Step 1: 17.6 cfm

Step 2: 9.5 cfm






Step 3: 17.6 cfm

Weight: 30 oz. with cord and plug

Accessories For Specific Tasks

Description	For use with				Part-No.	
	HS 3000 SLE	HG 2000 E	HL 2002 LR	HL 1502 E		
 Surface nozzle Provides an even air distribution on large surfaces.	2"	●	●	●	●	07011
	3"	●	●	●	●	07021
 Window nozzle Nozzle with reflector to direct air flow away from the glass to the flame.	2"	●	●	●	●	07031
	3"	●	●	●	●	07041
 39 mm (1-1/4") Reflector nozzle Reflects heat around a surface such as soldering copper pipe, bending PVC pipe, and heat shrink tubing.		●	●	●	●	07051
 Reduction nozzle Provides a totally concentrated pin point air flow.	3/8"	●	●	●	●	07062
	5/8"	●	●	●	●	07071
	3/4"	●	●	●	●	07081
 Plastic welding nozzle For working with flexible plastic welding wire. To be used with Item 07060.		●	●	●	●	07091
 Plastic welding rod nozzle Provides concentrated air flow to melt plastic welding rods. To be used with Item 07060.		●	●	●	●	07201
 20 mm (3/4") Slit nozzle For lap welding plastic materials. To be used with Item 07060.		●	●	●	●	07101
 75 mm (3") Heat disc Teflon coated disc for heating PVC pipe for butt welding. To be used with Item 07070.		●	●	●	●	07211
 Styrofoam cutting blade (5" Long) For making a clean cut in styrofoam. To be used with Item 07060.		●	●	●	●	07221
 75 mm (3") Reflector nozzle Reflects heat around a surface such as soldering copper pipe, bending PVC pipe and heat shrink tubing.		●	●	●	●	07301
 14 mm (5/8") Reflector nozzle Specially designed tip to provide efficient and quick heat to solder sink wire connectors.		●	●	●	●	07461
 40 mm (1-1/2") Slit nozzle For lap welding PVC sheeting and roofing material. To be used with Item 07070.		●	●	●	●	07471
 9 mm (3/8") Reflector nozzle For small diameter shrink tube applications.		●	●	●	●	07061
 40 mm (1-1/2") Angle slit nozzle Specially designed angle slit nozzle for efficiently lap welding single ply roofing materials.		●	●	●	●	07511
 Wire protection tube for hot air gun nozzle.		●	●	●	●	07401

Accessories Cont'd

	Description	Part-No.
	Plastic welding rods HDPE	07121
	Rigid PVC-welding-rods	07311
	Flexible PVC-welding-rods	07321
	Plastic welding rods LDPE	07331
	Plastic welding rods PP	07341
	Plastic welding rods ABS	07421
	Paint scraper set 5 pcs.	01031
	Spare blade set with 3 spare blades	01571
	Paint scraper handle	01331
	Feed roller For edging tape and PVC sheeting	01231

Hints on Hot Air Gun Uses

Forming and shaping

plastic materials

- Soften PVC pipe and other plastic materials for bending and shaping
- Soften vinyl floor coverings and around mouldings
- Soften formica coverings for shaping on rounded edges

Soldering

- Soldering copper pipe up to 3/4". Can use 90/10 solder
- Activate solder and wire connectors

Drying

- Quick drying of automotive body fillers
- Drying paint samples
- Drying plaster filling compounds

Thawing

- Thaw frozen water pipes
- Thaw frozen locks

Shrinking

- Shrinking shrink tube insulators
- Heat shrink PVC tubes
- Heat shrink packaging wrap

Roofing

- Heating modified bitumen
- Welding single ply material

Removal of adhesives

- Activating heat sensitive adhesives
- Removal of pressure sensitive stickers
- Removal of flooring adhesives

Other Uses

- Fiberglass work
- Wax removal on skies and surfboards
- Apply hot patches
- Paint stripping
- Softening hardened window glazing
- Plastic welding

CAUTION:

It is recommended that the user experiment on scrap materials before using for a specific task.