



[Search help](#)

HEI now offers a  
60 day 100% Total  
Satisfaction Guarantee.

Save \$\$ on our  
**Pre-Owned Tools**



[Currency Converter](#)

[Why Buy from HEI](#)

[Shopping Cart](#)



Call 1-800-394-1984

[Low Price Guarantee](#)

[Monthly Specials](#)

[Security Info](#)

Monthly Special  
HEI-MP4-FR



Stereo Zoom

**Microscopes**

[SZ Stereo Zoom](#)

[MZ Video Zoom](#)

[Binocular Pkgs.](#)

[Inspection Pkgs.](#)

**Boom Stands**

[Standard Boom](#)

[Dual Arm Boom](#)

[Post Stands](#)

[Track Stands](#)

[Articulating](#)

[Arms](#)

**E-Arms**

[76mm E-Arm](#)

[B&L E-Arm](#)

[Focus Racks](#)

**Illumination**

[Fluorescent Ring](#)

[Fiber Optic](#)

[Illuminator](#)

[Ring Light Guide](#)

[Pipe Light Guide](#)

[Back Light Guide](#)

[LED](#)

[Magnifier Lights](#)

**Monitors**

## HEIScope Boom Stands

HEIScope's standard duty boom stands have solid metal vertical and horizontal post with a locking ring on the vertical post for stopping. The diameter of the mounting hole on the front or the horizontal bar is 5/8". Each boom stand can be purchased with a standard base, big base, table clamp, or a U- base. All stands are industrial grade and offers quality performance.

### HEI-BS-SB



[Click for Large Image](#)

**\$225.00** [Buy Now](#)

### Standard Base Boom Stand

Weight	47lbs
Size of Base	11.22 x 10.236 x 0.709" (285 x 260 x 18mm)
Maximal size from vertical post to the front of base	9.38" (238.25mm)
Horizontal beam	19" (483mm) Diameter: 1.465" (37.2mm)
Vertical post	15.1" (384mm) Diameter: 1.465" (37.2mm)
Diameter of mounting holes in the front of horizontal beam	5 / 8" (15.875mm)
Maximal bearing load on the front of horizontal beam	21lbs 9.52kg

[Assembly Instructions for Boom Stand](#)

### HEI-BS-BB



[Click for Large Image](#)

**\$335.00** [Buy Now](#)

### Big Base Boom Stand

Weight	55 lbs
Size of Base	15.51 x 14.96 x .47" (394 x 380 x 12mm)
Maximal size from vertical post to the front of base	9.38" (238.25mm)
Horizontal beam	19" (483mm) Diameter: 1.465" (37.2mm)
Vertical post	15.1" (384mm) Diameter: 1.465" (37.2mm)
Diameter of mounting holes in the front of horizontal beam	5 / 8" (15.875mm)
Maximal bearing load on the front of horizontal beam	21lbs 9.52kg

[Assembly Instructions for Boom Stand](#)

[CRT Color Monitor](#)  
[LCD Color Monitor](#)

**[Accessories](#)**

[Frame Grabber](#)  
[USB Digital Camera](#)  
[CCD Color Camera](#)  
[Auxiliary Lens](#)  
[Eyepieces](#)  
[XY Tables](#)  
[Board Holders](#)  
[CCD Couplers](#)

**[Downloads](#)**

[Instruction Manuals](#)  
[Price List](#)

## HEI-BS-CB



[Click for Large Image](#)  
**\$250.00** [Buy Now](#)

## Standard Clamp Boom Stand

Weight	25 lbs
Maximal open size of clamp	1.575" (40mm)
Maximal size from vertical post to the front of base	9.38" (238.25mm)
Horizontal beam	19" (483mm) Diameter: 1.465" (37.2mm)
Vertical post	15.1" (384mm) Diameter: 1.465" (37.2mm)
Diameter of mounting holes in the front of horizontal beam	5 / 8" (15.875mm)
Maximal bearing load on the front of horizontal beam	21lbs 9.52kg
<a href="#">Assembly Instructions for Boom Stand</a>	

## HEI-BS-UB



[Click for Large Image](#)  
**\$250.00** [Buy Now](#)

## U-Base Boom Stand

Weight	23.37 lbs 10.6Kg
Size of Base	L x W x H = 450 x 360 x 30mm
Maximal size from vertical post to the front of base	9.38" (238.25mm)
Horizontal beam	19" (483mm) Diameter: 1.465" (37.2mm)
Vertical post	15.1" (384mm) Diameter: 1.465" (37.2mm)
Diameter of mounting holes in the front of horizontal beam	5 / 8" (15.875mm)
Maximal bearing load on the front of horizontal beam	21lbs 9.52kg
<a href="#">Assembly Instructions for Boom Stand</a>	

[Home](#) | [Packages](#) | [Video Inspection](#) | [Monthly Special](#) | [Stands](#) | [E-Arms](#) | [Illumination](#) | [Monitors](#) | [Accessories](#)  
[Eye Pieces](#) | [Auxiliary Lenses](#) | [CCD Camera](#) | [XY Table](#) | [Magnifiers](#) | [Price List](#) | [Contact us](#) | [Warranty](#)

[Home](#) | [Catalogs by Manufacturer](#) | [Products](#) | [Our Customers](#) | [Free Trial](#) | [Search Form](#) | [Table of Contents](#) | [Information Downloads](#) | [Shopping Cart](#) | [Articles of Interest](#) | [Currency Conversion Chart](#) | [Shop Safe Guarantee](#) | [Pre-Owned Tools](#) | [Receive Newsletter](#) | [Cost Cutting Specials](#)

**Howard Electronic Instruments, Inc.**

974 SE Pioneer Rd  
 El Dorado, KS 67042

**1-800-394-1984** Toll Free (USA and Canada)

01-316-321-2800 International Phone

316-321-2803 Fax

[Contact Us](#)

[Our Shop Safe Guarantee](#)

[Shopping Cart Help?](#)

Copyright © 1996 - 2005 Howard Electronic Instruments, Inc. All rights reserved.

Revised: February 02, 2005.

