

SAI Global File #004008

Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Super Wick No Clean

SDS Code: 400-NS Series

Related Part # 424-NS, 424-NS-10, 425-NS, 425-NS-10, 426-NS, 426-NS-10, 453-NS,

454-NS

Recommended Use and Restriction on Use

Use: No clean desoldering braid

Uses Advised Against: Do not use brazing soldering methods such as high temperature

torch soldering/torch welding.

Details of Manufacturer or Importer

Manufacturer

MG Chemicals MG Chemicals (Head Office) 1210 Corporate Drive 9347-193 Street

Surrey, British Columbia V4N 4E7 Burlington, Ontario L7L 5R6

CANADA CANADA

***** +1-800-340-0772 **~** +1-905-331-1396 +1-905-331-2682 FAX +1-800-340-0773 FAX support@mgchemicals.com E-MAIL info@mgchemicals.com E-MAIL

WEB www.mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents

USA or CANADA: Call CHEMTREC **☎**: +1-800-424-9300

For emergencies involving dangerous goods; Collect 24/7

CANADA: Call CANUTEC **2**: +1-613-996-6666 or *666 on cellular phones

Date of Revision: 16 March 2017 / Ver. 3.01

SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Respiratory	1	Danger	Health
Sensitization	Skin	1	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from

1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
	H317: May cause an allergic skin reaction
Prevention	Precautionary Statements
P261	Avoid breathing fumes/vapors.
P284	In case of inadequate ventilation wear respiratory protection.
P280	Wear protective gloves.
P272	Contaminated work clothing should not be allowed out of the workplace.
Response	Precautionary Statements
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Continued ...

Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-50-8	copper	99.9%
8050-09-7	rosin, colophony	0.1%

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF INHALED	P304 + P340, P342 + P311
Immediate Symptoms	cough, headache, sore throat, wheezing
Response	Remove person to fresh air and keep comfortable for breathing.
	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	mild irritation, redness
Response	Wash with plenty of water.
	If skin irritation or rash occurs: Get medical advice.
	Take off contaminated clothing and wash it before reuse.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	redness, mild irritation
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Continued ...

IF SWALLOWED P301 + P330, P331

Immediate Symptoms abdominal pain, nausea, vomiting

Response Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire: Use extinguish media suitable for surrounding.

Specific Hazards In a fire, this product can release irritating flux fumes.

Do NOT use water on fires where molten metal is present.

Combustion Products Produces carbon oxides (CO and CO₂).

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for

Avoid breathing fumes/vapors. Remove or keep away all

sources of extreme heat.

Environmental

Response

Precautions

Avoid releasing to the environment.

Containment Methods Not applicable

Cleaning Methods Collect waste in a sealable waste container.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Avoid breathing fumes/vapors.

Do not eat, drink, or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Handling In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Take off contaminated clothing and wash it before reuse. Wash hands

thoroughly after handling.

Avoid release to the environment.

Storage Not applicable.



SAI Global File #004008

Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
copper (dust and mist)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1.0 mg/m ³ 1.0 mg/m ³ 1.0 mg/m ³ 1.0 mg/m ³ 1 mg/m ³ 1 mg/m ³	Not established Not established Not established Not established Not established Not established
rosin, colophony (solder thermal decomposition)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	L, S, asthma Not established Not established L, S L 0.1 mg/m ³	Not established Not established Not established Not established Not established Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

- (L) Exposure by all routes should be carefully controlled to levels as low as possible.
- (S) Sensitizer

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Manufacturer's Note: Soft soldering temperatures (<450 °C) are generally too low to generate significant amounts of metal vapors, but dust, metal oxide, or flux decomposition fumes can occur.

For frequent or prolonged soldering processes, use of a local exhaust system to avoid exposure to thermal decomposition products. For example, use fume cabinet, a hood on a flexible arm, or tip-mounted fume extraction system on the soldering iron.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

Recommendation: Ensure that glasses have side shields for

lateral protection.

Skin Protection For incidental contacts, use nitrile or other chemically resistant

gloves. Thermal resistant gloves should be worn instead if

contact with molten metal is expected.

Respiratory Protection If exposed to fumes or dust above the exposure limit, a

suitable wear respirator meeting local/regional/national

guidelines.

Generally, for emergencies and exposure above 0.5 mg/m³, use a self-contained breathing apparatus with full face piece

operated in a pressure positive mode.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the

ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not applicable
Appearance	Copper	Upper Flammability Limit	Not applicable
Odor	None	Vapor Pressure @20°C	Not available
Odor Threshold	Not available	Vapor Density	Not applicable
pH	Not available	Specific Gravity @25 °C	8.8
Freezing/Melting	1 057 °C	Solubility in	Negligible ^{a)}
Point	[1 934 °F]	Water	
Boiling Point	Not	Partition	Not
	available	Coefficient	available
Flash Point	Not	Auto-ignition	Not
	applicable	Temperature	available
Evaporation	Not	Decomposition	Not
Rate	available	Temperature	available
Flammability	Not	Viscosity	Not
(solid, gas)	applicable	@25 °C	applicable

a) Metal components are sparingly soluble

Section 10: Stability and Reactivity

Reactivity Shock sensitive compounds are formed with azides, ethylene oxides,

and acetylenic compounds. Reacts strongly with chlorate, bromate,

or iodate oxydants causing explosion hazards.

Chemical Stability

Chemically stable at normal temperatures and pressures

Conditions to

Avoid

Extreme temperatures above 450 °C, such as those due to welding

Incompatibilities Oxidizing agents, strong acids, halogens

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 11: Toxicological Information

Routes of Exposure

Inhalation, Skin contact, Eye contact, and Ingestion

Symptoms Summary

Eyes May cause mild irritation and redness.

Skin May cause mild irriation and redness.

Inhalation May cause cough, headache, sore throat and wheezing.

Additional Desoldering By-Product Information: Overexposure to dust or

metal fumes from the solders may lead to pneumoconiosis (or

Stannosis), anemia and central nervous system effects.

Ingestion May cause abdominal pain, nausea and vomiting

Chronic Prolonged or repeated exposure to the oxidized rosin flux may lead to

skin sensitization, respiratoy sensitization and provoke asthma.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
copper	>5 000 mg/kg	Not	>5.11 mg/L
	Mouse	available	Rat 4 h
rosin, colophony	≥2 800 mg/kg	≥2 000 mg/kg	110 mg/m³
	Rat	Rat	Rat

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier (M)SDS were also consulted.

Other Toxicological Effects

Skin corrosion/irritation Based on available data,

the classification criteria are not met.

Serious eye Based on available data,

damage/irritation the classification criteria are not met.

Sensitization May cause respiratory and skin sensitization when in (allergic reactions) contact with the oxidized form of rosin. Rosin is

classified as skin sensitizer due to its continued

inclusion in many regulatory lists.



SAI Global File #004008 Burlington, Ontario, Canada

Super Wick No Clean 400-NS Series

Carcinogenicity Not classified or listed as a carcinogen by IARC, ACGIH,

(risk of cancer) CA Prop 65, or NTP

Mutagenicity Based on available data,

(risk of heritable genetic the classification criteria are not met.

effects)

Reproductive Toxicity Based on available data,

(risk to sex functions) the classification criteria are not met.

Teratogenicity (risk of fetus Based on available data,

malformation) the classification criteria are not met.

STOT-single exposure Based on available data,

the classification criteria are not met.

STOT-repeated exposure Based on available data,

the classification criteria are not met.

Aspiration hazard There is no category 1 components, and the kinematic

viscosity is $>20.5 \text{ mm}^2/\text{s}$ at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable

Based one transformation/dissolution data published by ECHA registrants, the classification threshold is not met for massive copper.

Based on available data for rosin, the GHS aqueus toxicity classification criteria are not met.

Acute Ecotoxicity

See Chronic Ecotoxicity

Chronic Ecotoxicity

Non hazardous

Biodegradability

Not available

Bioaccumulation

Not available

Other Effects

Not available



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Non Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Non Regulated

Sea

Refer to IMDG regulations.

Non Regulated

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.



SAI Global File #004008

Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

USA

Other Classifications

HMIS® RATING

HEALTH:	1
FLAMMABILITY:	0
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains copper (CAS# 7440-50-8; reportable quantity = 5000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any of the listed substances.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is subject to the WEEE regulation.



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Section 16: Other Information

SDS Prepared by Michel Hachey **Date of Review** 16 March 2017 Supersedes 10 August 2016

Reason for Changes: Additional part numbers added

Reference

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support Head Office

> 1210 Corporate Drive 9347-193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Section continued on the next page

Page **12** of **13**

Date of Revision: 16 March 2017 / Ver. 3.01



SAI Global File #004008 Burlington, Ontario, Canada

SUPER WICK NO CLEAN

400-NS SERIES

Disclaimer

This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.