



STEINEL · 9051 Lyndale Avenue South · Bloomington · MN 55420 Telephone 800-852-4343 · Fax 952-888-5132 · www.steinel.net · sales@steinel.net

HG 350 ESD

Precision Hot Air Tool

The HG 350 ESD is the ultimate precision hot air tool.

This sleek, ergonomically optimized tool incorporates cutting edge STEINEL technology to meet the exacting needs of even the most sensitive applications. Innovative features include a bright LED light to illuminate the work area while highly focused hot air ensures an accurate result.

STEINEL...for world-class performance, guaranteed.

Introducing STEINEL Precision Hot Air Tool

STENEL

STEINEL Precision Hot Air Tool

STEINEL Precision Hot Air Tool

HG 350 ESD





LED light provides bright illumination of the work area and also serves as a convenient "on" indicator



Optimised weight balance ensures fatigue-free long term operation

HG 350 ESD

Precise Output

- Targeted 3.5 CFM airflow
- 750 °F Temperature (930 °F with included 1/4" / 7mm Reducer)
- LED light illuminates work area

Ergonomically Optimised

- Sleek, balanced design for comfortable long-term use
- Compact, lightweight construction
- Built-in security hanger for overhead suspension

Integrated Safety

- ESD safe
- LED serves as a convenient "on" indicator
- Safety rests help prevent surface contact with hot nozzle

Accessories



Item No. 07730

1/4" / 7mm Reducer

Included with tool



Item No. 07735

Reducer with

Reflector Guard

For desoldering

electronic compounds



Item No. 07765

1 1/2" / 40mm Reflector

For shrink tubing &

solder sleeves





2/5" / 10mm Reflector

For shrink tubing &

solder sleeves

Precision Reflector

For shrink tubing & solder sleeves









Ideal for de-soldering electronic components


Variety of reflectors available for specific shrink tube and solder sleeve applications

Made in E.U. 💬 🚟 🖾 ISO 9001-2000

190 9001:2000		Specifications
	Item No.	34735
	Dimensions (h x w x d)	9 1/2" x 2 1/2" x 7"
	Weight	Approx. 660 g
	Voltage	120 VAC / 60 Hz
	Output	300 W
	Temperature	750 °F without nozzle 930 °F with 7mm Reducer (included)
	Airflow rate	3.5 CFM
	Power cord	Industrial grade rubber, length: 6 ft.

Constituentie





Integral security hanger for safety and convenience

HG 350 ESD

